





STATIONARY NG/LP FIRED PRESSURE WASHER | Specifications:

GENERAL						ELECTRICAL			BURNER SYSTEM		DIMENSIONS/WEIGHT			
Model	Туре	GРM	PSI	НР	Drive	Volt	Amp	Ph	вти	Stack Size	L	w	н	Lb
16-310	ES/SC	3	1000	2.3	Belt	115	20	1	306,016/320,000	10"	39"	26"	46"	430
16-325	ES/SS/SC	3	2500	5	Belt	230	20	1	306,016/320,000	10"	39"	26"	46"	445
16-423	ES/SS/SL/SC	4	2300	6	Belt	230/440	20/30/15	1/3	420,772/415,000	10"	39"	26"	46"	630
16-430	ES/SS/SL/SC	4	3000	8/7.5	Belt	230/440	40/25/15	1/3	420,772/415,000	10"	39"	26"	46"	650
16-525	ES/SS/SL/SC	5	2500	8/7.5	Belt	230/440	40/25/15	1/3	420,772/440,000	10"	39"	26"	46"	670
16-530	SL/SS/SLC	5	3000	10	Belt	230/440	50/25/15	1/3	420,772/440,000	10"	39"	26"	46"	720
16-625	SL/SS/SLC	6	2500	10	Belt	230/440	60/40/20	1/3	420,772/440,000	10"	39"	26"	46"	720

Features (not shown on breakout):

ES Model Features:

- 115V 1 Phase (16-310ES)
- 230V 1 Phase (16-325ES/16-425ES/16-525ES)
- · Fuel Efficient Combustion Chamber
- **Exclusive Chamber Insulation System**
- ASTM A53 Schedule 80 Steel Heating Coil
- · Heavy Duty Electro Plated Fittings
- High Limit Temp. Control
- Insulated Wand w/4000 PSI Trigger Gun
- 0° & 15° Quick Couple Stainless Steel **Nozzles**
- · Trigger Gun Control

- 3/8" x 50' High Pressure Hose w/Safety Hose Guards
- · Wire Braid Discharge Hose
- Low Water Shutoff Protection
- · Watertight Electrical Panel
- · Draft Diverter

SS - Includes All the Features of ES Plus:

- 230V 1 Phase
- · High Pressure Soap
- ETL Listed

SL - Includes All the Features of SS Plus:

- Time Delay Shutdown
- · Hour Meter
- 0°. 15°. 25° & 40° Quick Coupled Nozzles

SC - Includes All the Features of SS Plus:

· Clutch Drive

SLC - Includes All the Features of SS Plus:

· Clutch Drive

· Time Delay Shutdown



A Closer Look at the Features:



Hour Meter Allows you to keep track for periodic maintenance (Option Not Shown)



Exclusive Coil Design
Heats water
quicker & more
efficiently.



Soap Control Allows for the precise metering of your expensive soap.

Stainless Steel Combustion Chamber Maintenance



free, durable protection. Adjustable Temp. Control
For your
precise temp.
control.



Panel Mounted Controls your ease of



Stainless Steel Nozzles Panel mounted to be handy & accessible.



Durable Powder Coated Heavy Duty Modular Frame For years of maintenance

free service & protection of the unit's internal parts.





















Configured for you by:

