



CLEANING SYSTEMS

GAS DRIVEN, OIL FIRED SELF CONTAINED PRESSURE WASHER | Specifications:

G	ENGINE/BURNER SYSTEM						DIN	DIMENSIONS/WEIGHT						
Model	GPM	PSI	HP	Drive	Volt	Engine	Engine Start	Fuel Engine/ Burner	BTU	Stack Size	L	w	н	Lb
42-430H / 42-430GH	4	3000	13	Belt	12/110	Honda	Electric	Gas/Oil	384,000	8"	43"	34"	43"	725/850
42-430H-C / 42430GH-C	4	3000	13	Clutch	12/110	Honda	Electric	Gas/Oil	384,000	8"	43"	34"	43"	740/865
42-440V / 42-440GV	4	4000	16	Belt	12/110	Vanguard	Electric	Gas/Oil	384,000	8"	43"	34"	43"	750/850
42-440H / 42-440GH	4	4000	20	Belt	12/110	Honda	Electric	Gas/Oil	384,000	8"	43"	34"	43"	750/850
42-530V / 42-530GV	5	3000	16	Belt	12/110	Vanguard	Electric	Gas/Oil	465,000	8"	43"	34"	43"	750/820
42-530V-C / 42-530GV-C	5	3000	16	Clutch	12/110	Vanguard	Electric	Gas/Oil	465,000	8"	43"	34"	43"	765/835
42-535H / 42-535GH	5	3500	20	Belt	12/110	Honda	Electric	Gas/Oil	465,000	8"	43"	34"	43"	800/865
42-530H-C / 42-530GH-C	5	3000	20	Clutch	12/110	Honda	Electric	Gas/Oil	465,000	8"	43"	34"	43"	815/880
42-830V / 42-830GV	8	3000	23	Belt	12/110	Vanguard	Electric	Gas/Oil	547,000	8"	43"	34"	43"	1015/1080
42-830V-C / 42-830GV-C	8	3000	23	Clutch	12/110	Vanguard	Electric	Gas/Oil	547,000	8"	43"	34"	43"	1015/1080

Features (not shown on breakout):

- Quick Couple Stainless Steel Nozzles
- ASTM A53 Schedule 80 Steel Heating Coil
- Trigger Gun Control

Notes:

- Variable Pressure Wand (42-430/42-530)
- Wire Braid Discharge Hose
- Low Oil Engine Protection
- Water Separating Fuel Filter
- Low Water Shutoff Protection
- Automatic Electric Burner Ignition
- A Closer Look at the Features:

- Extended Engine Oil Drain (Vanguard)
- Auxiliary Gasoline Tank (42-440/42-530/42-830)
- Shock Mount Plastic Battery Box
- Stainless Steel Control Panel

12V H Models

- High Amp Charging System
- 12V Ignition System
- Downstream Chemical Injection

110V GH Models

- Calibrated Detergent Mixing Valve
- High Pressure Soap
- Circuit Breaker Protected
- Stainless Steel Float Tank



Configured for you by:

В

E

ΤE

