





SELF CONTAINED PRESSURE WASHER | Specifications:

GENERAL						ENGINE/BURNER SYSTEM					DIMENSIONS/WEIGHT			
Model	GРM	PSI	НР	Drive	Volt	Engine	Engine Start	Fuel Engine/ Burner	вти	L	w	н	Lb	
47-1028GLDD-C	10	2800	24.8	Belt	120	Kubota	Electric	Diesel/Diesel	860,000	53"	43"	50.5"	1745	

Features (not shown on breakout):

- · Automotive Quality Powder Coat Frame
- · Heavy Duty Insulated Cabinet Frame
- Removable Access Panels
- Recessed Control Panel
- · Diagnostic Controls
- · Amp Meter
- **Downstream Chemical Injection**
- Murphy Switch Control System
- Electric Start

- · Shock Absorbing Engine Base
- · Plastic Battery Box
- Triplex Ceramic Plunger Pumps
- Thermal Pump Protection
- Dual Horizontal Fuel Efficient Combustion
- ASTM A53 Schedule 80 Steel Heating Coil
- · High Efficiency Beckett Pressure Atomized Burners
- Automatic Electric Burner Ignition
- · Water Separating Fuel Filters
- Trigger Gun Control
- (2) 3/8" x 50' High Pressure Hose Assemblies
- (2) Adjustable Dual Lance Wands
- · Quick Couple Stainless Steel Nozzles



A Closer Look at the Features:



Hour Meter Allows you to keep track for periodic maintenance.



Adjustable Temp. For your precise temp. control.



Panel Mounted Controls Handy & accessible for your ease of use.



Dual Gun Outlets Front mounted for easy











Stainless Steel Chamber Cover & Powder Coated Side Panels Maintenance free durable protection.



Exclusive Coil Design Heats water quicker & more efficiently.



Forklift Pockets Provides for safe & easy movement.



ide Cabinet (Not Shown)



Generator your use of a 110V



Optional Clutch Drive Save money by lengthening the life of your pump.



Industrial Strength Triplex Pumps
Lower maintenance costs due to long life & durability.



Dual Pressure Prevents injury & cost due to an over-pressurized system.

This unit is equipped with an extra large 40 Gallon 1/8" steel fuel tank to provide a longer operation duration.

Configured for you by: Notes:

