

COLD WATER PRESSURE WASHER | Specifications:

GENERAL						ELECTRICAL			INCLUDED ACCESSORIES		DIMENSIONS/ WEIGHT			
Model	Туре	GPM	PSI	HP	Drive	Volt	Amp	Ph	Nozzle	Hose	L	W	Н	Lb
521.6	SBD/SBDC	2	1600	2.3	Belt/Clutch	115	20	1	0°, 15°, 25°, 40°, Soap	3/8" x 50'	33"	25"	40.5"	175
531	SBD/SBDC	3	1000	2.3	Belt/Clutch	115	20	1	0°, 15°, 25°, 40°, Soap	3/8" x 50'	33"	25"	40.5"	175
532.5	SBD/SBDC	3	2500	5	Belt/Clutch	230	20	1	0°, 15°, 25°, 40°, Soap	3/8" x 50'	33"	25"	40.5"	177
542.3	SBD/SBDC/SBDSLC	4	2300	6	Belt/Clutch	230	30	1	0°, 15°, 25°, 40°, Soap	3/8" x 50'	33"	25"	40.5"	238
543	SBD/SBDC/SBDSLC	4	3000	8	Belt/Clutch	230	40	1	0°, 15°, 25°, 40°, Soap	3/8" x 50'	33"	25"	40.5"	258
552.5	SBD/SBDC/SBDSLC	5	2500	8	Belt/Clutch	230	40	1	0°, 15°, 25°, 40°, Soap	3/8" x 50'	33"	25"	40.5"	282
553	SBD/SBDC/SBDSLC	5	3000	10	Belt/Clutch	230	50	1	0°, 15°, 25°, 40°, Soap	3/8" x 50'	33"	25"	40.5"	325

Features (not shown on breakout):

- Well Balanced Design for Easy Maneuverability
- Durable Powder Coated Automotive Quality
 Paint Finish
- Flat-Free Tires w/Solid Micro-Cellular Polyurethane
- Rear Wheel Locking Brake System

Notes:

- Welded Heavy Duty 1 1/4" OD Steel Tube Frame
- Built-In Hose Reel Socket
- Built-In Gun Cup
- Belt Driven Tri-Plunger Ceramic Piston
 Pump
- Heavy Duty Electro Plated Fittings
- Exclusive High Strength Plastic Manifold
- Quick Couple Plumbing Connections
- Stainless Steel Electrical Control Panel
- Heavy Duty Rotary Power Switch

- Trigger Gun Control w/36" Insulated Wand
- 3/8" x 50' High Pressure Hose Assembly w/ Safety Hose Guards
- Flexible Vinyl Poly Coated Tri-Lingual Decals





Configured for you by:

