







SELF CONTAINED COLD WATER PRESSURE WASHER | Specifications:

GENERAL						ENGINE	SYSTEM		MISCELLANEOUS		
Model	GРM	PSI	HP	Drive	Volt	Engine	Engine Start	Engine Fuel	Nozzle	Hose	Weight
51-430-CR/SS	4	3000	16	Belt/Clutch	12	Vanguard	Electric	Gas	0°, 15°, 25°, 40°	3/8" x 50'	330
51-530-CR/SS	5	3000	16	Belt/Clutch	12	Vanguard	Electric	Gas	0°, 15°, 25°, 40°	3/8" x 50'	330
51-630-CR/SS	6	3000	18	Belt/Clutch	12	Vanguard	Electric	Gas	0°, 15°, 25°, 40°	3/8" x 50'	330
51-830-CR/SS	8	3000	23	Belt/Clutch	12	Vanguard	Electric	Gas	0°, 15°, 25°, 40°	3/8" x 50'	330
51-1030-CR/SS	10	3000	31	Belt/Clutch	12	Vanguard	Electric	Gas	0°, 15°, 25°, 40°	3/8" x 50'	378

Features:

- 12V Ignition System
- · Heavy Duty Skid Frame
- Trigger Gun Control
- Panel Mounted Controls

- Trigger Gun Control
- Pressure Relief Valve
- Wire Braid Discharge Hose
- Stainless Steel Tips

- Automotive Quality Powder Coat Finish
- · Standard Clutch Drive
- Triplex Ceramic Plunger Pump



A Closer Look at the Features:



Durable Stainless Steel or Powder Coated Industrial Frame Extreme rust resistance.



Vanguard Engine • Time proven dependability.



Electric Start Allows for quick & easy operation without pull cord strain.



Optional Clutch Drive Save money by lengthening the life of your





Pressure Relief Valve Prevents injury & cost due to an over-pressurized system.



Industrial
Strength Triplex
Pump
Lower maintenance
costs due to long
life & durability.



Stainless
Steel Nozzles
Panel
mounted to
be handy &
accessible.



Poly Fuel
Tank
Prevents
corrosion
saving costly
replacement.



Notes: Configured for you by:

