





SELF CONTAINED COLD WATER PRESSURE WASHER | Specifications:

GENERAL					ENGINE SYSTEM				MISCELLANEOUS		
Model	GРM	PSI	НР	Drive	Volt	Engine	Engine Start	Engine Fuel	Nozzle	Hose	Weight
52-630-CR/SS	6	3000	18	Belt/Clutch	12	Vanguard	Electric	Gas	0°, 15°, 40°	3/8" x 50'	440
52-830-CR/SS	8	3000	23	Belt/Clutch	12	Vanguard	Electric	Gas	0°, 15°, 40°	3/8" x 50'	440
52-1030-CR/SS	10	3000	31	Belt/Clutch	12	Vanguard	Electric	Gas	0°, 15°, 40°	3/8" x 50'	488
52-1230-CR/SS	12	3000	35	Belt/Clutch	12	Vanguard	Electric	Gas	0°, 15°, 40°	3/8" x 50'	488

Features:

- 12V Ignition System
- · Heavy Duty Skid Frame
- Trigger Gun Control
- Panel Mounted Controls

- Trigger Gun Control
- Pressure Relief Valve
- · Wire Braid Discharge Hose
- Stainless Steel Tips

- · Automotive Quality Powder Coat Finish
- · Standard Dual Clutch Drive
- Triplex Ceramic Plunger Pump



A Closer Look at the Features:



Durable Stainless Steel or Powder Coated Industrial Frame Extreme rust resistance.



Vanguard Engine Time proven dependability.



Electric Start Allows for quick & easy operation without pull cord strain.



Dual Clutch Drives
Save money
by lengthening
the life of your





Dual Outlets Allows two wands to run at the same



Poly Fuel Tank Prevents corrosion saving costly replacement.

Pressure Relief Valve Prevents injury & cost due to an over-pressurized





Stainless Stainless
Steel Nozzles
Panel
mounted to
be handy &
accessible.



Dual Controls Independent operation of each pump.



Configured for you by: Notes:

