





OIL FIRED PORTABLE PRESSURE WASHER | Specifications:

GENERAL							ELECTRICAL			BURNER SYSTEM		DIMENSIONS/WEIGHT			
Model	Туре	GPM	PSI	HP	Drive	Volt	Amp	Ph	BTU	Stack Size	L	w	н	Lb	
12-203D	ED	2	300	.75	Direct	115	20	1	179,000	8"	31.5"	24.5"	39"	290	
12-212	ED	2	1200	2	Direct	120	20	1	175,000	7"	31.5"	24.5"	39"	300	
12-320D	ED	3	2000	4	Direct	230	20	1	269,000	7"	31.5"	24.5"	39"	320	
12-303D	ED	3	300	.75	Direct	115	15	1	383,000	8"	37.5"	29"	44.5"	380	
12-210CD	ED	2.2	300/1000	1.5	Direct	115	20	1	383,000	8"	37.5"	29"	44.5"	415	
12-216	ES/EL	2	1600	2.3	Belt	120	20	1	175,000	7"	31.5"	24.5"	39"	310	
12-310	ES/EL	3	1000	2.3	Belt	115	20	1	269,000	7"	31.5"	24.5"	39"	310	
12-325	ES/EL	3	2500	5	Belt	230	20	1	269,000	7"	31.5"	24.5"	39"	325	
12-416	ES/EL	4	1600	6	Belt	230	30	1	384,000	8"	37.5"	29"	44.5"	540	
12-423	ES/EL	4	2300	6	Belt	230	30	1	384,000	8"	37.5"	29"	44.5"	465	
12-430	ES/EL	4	3000	8	Belt	230	40	1	384,000	8"	37.5"	29"	44.5"	485	

Features (not shown on breakout):

- **ED Model Features:**
- · Heavy Duty Electro Plated Fittings
- Built-In Hose Reel Socket
- 3/8" x 40' High Pressure Hose
- · Four Wheel Design
- ASTM A53 Schedule 80 Steel Heating Coil
- · Fuel Oil Solenoid
- · In-Line Fuel Filter
- Trigger Gun Control
- 36" Insulated Wand

- Flood Nozzle w/Fixed 15° Spray Tip
- · GFCI Protection w/10' Electrical Cord

ES - Includes All the Features of ED Plus: Belt Driven Pump

- Exclusive High Strength Nylon Manifold Quick Couple Manifold Plumbing Connections
- · Polyethylene Fuel Tank w/Chemical Metering
- 0° & 15° Quick Couple Nozzles

EL - Includes All the Features of ED Plus:

- Stainless Steel Belt Guard & Wrapper
- Stainless Steel Electrical Control Panel
- · Water Separating Fuel Filter
- 3/8" x 50' High Pressure Hose
- GFCI Protection w/36'Electrical cord (except 12-430)
- · In-Line Fuel Shutoff
- · Accessory Package

