





OIL FIRED PORTABLE PRESSURE WASHER | Specifications:

GENERAL						ELECTRICAL			BURNER SYSTEM		DIMENSIONS/WEIGHT			
Model	Туре	GPM	PSI	НР	Drive	Volt	Amp	Ph	BTU	Stack Size	L	w	н	Lb
14-310C	SS	3	1000	2.3	Belt	115	20	1	479,000	8"	37.5"	29"	44.5"	540
14-320C	SS	3	2000	4	Belt	230	20	1	479,000	8"	37.5"	29"	44.5"	560
14-423	SS/SL/SC	4	2300	6/7.5	Belt	230/440	30/20/15	1/3	384,000	8"	37.5"	29"	44.5"	535
14-430	SS/SL/SC	4	3000	8/7.5	Belt	230/440	40/30/20	1/3	384,000	8"	37.5"	29"	44.5"	545
14-518	SS/SC	5	1800	6.0	Belt	230	30	1	437,000	8"	37.5"	29"	44.5"	545
14-525	SS/SL/SC	5	2500	8/7.5	Belt	230/440	40/30/20	1/3	437,000	8"	37.5"	29"	44.5"	605
14-530	SS/SL/SC	5	3000	10	Belt	230	50	1	437,000	8"	37.5"	29"	44.5"	655

SS Features (not shown on breakout):

- Well Balanced for Easy Maneuverability
- · Powder Coated Automotive Quality Finish
- Rear Wheel Locking Brake System
- Built-In Hose Reel Socket
- · Heavy Duty Electrical Cord & Hose Storage
- · Built-In Gun Cup
- · Stainless Steel Belt Guard
- Heavy Duty Electro Plated Fittings
- Exclusive High Strength Plastic Manifold
- **Quick Couple Plumbing Connections**

- · Heavy Duty Rotary Power Switch
- ASTM A53 Schedule 80 Steel Heating Coil
- Quick Coil Access
- · Fuel Oil Solenoid
- · Water Separating Fuel Filter
- In-Line Fuel Shutoff
- Trigger Gun Control w/36" Insulated Wand
- 0°, 15°, 25°, & 40° Quick Coupled Nozzles
- 3/8" x 50' High Pressure Hose w/Safety Hose Guards
- · Flexible Vinyl Poly Coated Tri-Lingual Decals
- ETL and CETL Listed to UL Std.1776 & CSA Std. B140.11 (Except 40 & 50 Amp Single Phase Models in Standard Form)

SC - Includes All the Features of SS Plus:

· Clutch Drive System



Notes:



THORIZED